

**FLEXTILE LTD**  
**Material Safety Data Sheet**

**FLEXEPOXY 100 - PART A**

**Material Identification and Use**

MANUFACTURER/SUPPLIER'S NAME.....	FLEXTILE LTD.
MANUFACTURER'S ADDRESS.....	121-30TH STREET, ETOBICOKE, ONT. M8W 3C1
MANUFACTURER'S PHONE NUMBER.....	(416)255-1111 Toll-Free 1-800-699-3623 FAX: (416)255-1729
IN CASE OF CHEMICAL EMERGENCY.....	CALL CANUTEC (631)996-666
PRODUCT IDENTIFIER.....	FLEXEPOXY 100 - PART A
PRODUCT USE.....	100% SOLIDS EPOXY GROUTING & SETTING COMPOUND
WHMIS CLASSIFICATION.....	CLASS D, DIVISION 2A

**Hazardous Ingredients of Materials**

CHEMICAL IDENTITY % PERCENT	CAS#/NA#/UN#	OSHA (PEL)	ACGIH (TLV-TWA)
SILICA SAND 60-100%	13463-67-7	10 mg/m <sup>3</sup>	0.1 mg/m <sup>3</sup>
EPOXY RESIN 10-30 %	25068-38-6	N/E	N/E
NEODOL GLYCIDYL ETHER 3-7 %	120547-52-6	N/E	N/E

All ingredients are listed within or exempted from US TSCA and Canadian DSL

**Physical Data For Product**

PHYSICAL STATE.....	PASTE
ODOR AND APPEARANCE.....	FAINT EPOXY ODOR
ODOR THRESHOLD.....	N/D
SPECIFIC GRAVITY.....	1.83
VAPOR PRESSURE.....	< 1.0 AT 20 DEG C
VAPOR DENSITY (air=1).....	1.0 (HEAVIER THAN AIR)
EVAPORATION RATE.....	SLOWER THAN ETHER
BOILING POINT.....	N/D
FREEZING POINT.....	N/D
pH.....	N/D
DENSITY (g/ml).....	N/D
PERCENT VOLATILE (BY WEIGHT).....	N/D

**Fire and Explosion Hazard of Product**

CONDITIONS OF FLAMMABILITY.....	STABLE
MEANS OF EXTINCTION.....	FOAM, CO2, DRY CHEMICAL.
FLASHPOINT AND METHOD OF DETERMINATION.....	>100C (T.C.C)
UPPER EXPLOSION LIMIT (% BY VOL)..	N/D
LOWER EXPLOSION LIMIT (% BY VOL)..	N/D
AUTO-IGNITION TEMPERATURE.....	N/D

**SPECIAL FIRE-FIGHTING PROCEDURES..**

MATERIAL WILL NOT BURN UNLESS PREHEATED. AVOID INHALATION OF SMOKE. DO NOT ENTER CONFINED FIRE SPACE WITHOUT ADEQUATE PROTECTIVE CLOTHING AND AN APPROVED POSITIVE SELF-CONTAINED BREATHING APPARATUS. USE WATER TO COOL FIRE EXPOSED CONTAINERS.

SENSITIVITY TO STATIC DISCHARGE...	NO
------------------------------------	----

**Reactivity Data**

CHEMICAL STABILITY.....	STABLE
INCOMPATIBLE MATERIALS.....	NO SPECIFIC INCOMPATIBILITIES
CONDITIONS TO AVOID.....	EXCESSIVE HEAT OVER LONG PERIODS.

FLEXEPOXY 100 - PART A

**HAZARDOUS COMBUSTION/DECOMPOSITION PRODUCTS..**

**WHEN HEATED TO DECOMPOSITION, IT MAY EMIT TOXIC FUMES. CARBON DIOXIDE, CARBON MONOXIDE, ALDEHYDES AND ACIDS MAY BE FORMED DURING COMBUSTION. REACTION WITH SOME CURING AGENTS MAY PRODUCE CONSIDERABLE HEAT WHICH COULD CHAR THE REACTION MASS AND PRODUCE FUMES AND VAPOURS IF UNKNOWN COMPOSITION.**

**Toxicological Properties of Product**

**ROUTES OF ENTRY**

**EXPOSURE MAY OCCUR VIA INHALATION, INGESTION OR THROUGH SKIN CONTACT. THIS PRODUCT IS EXPECTED TO BE A SKIN SENSITIZER, AS WELL AS IRRITATING TO BOTH THE SKIN AND EYE.**

**SUPPLEMENTAL HEALTH INFORMATION...**

**PRODUCT IRRITATING TO THE SKIN AND EYES. VAPORS ARE MODERATELY IRRITATING TO THE EYES AND RESPIRATORY PASSAGES. PROLONGED AND REPEATED CONTACT WITH SKIN CAN CAUSE DEFATTING AND DRYING OF THE SKIN RESULTING IN SKIN IRRITATION AND DERMATITIS. SKIN SENSITIZATION MAY OCCUR FOLLOWING REPEATED CONTACT. PREEXISTING EYE, SKIN AND RESPIRATORY DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT. PREEXISTING SKIN OR LUNG ALLERGIES MAY INCREASE THE CHANCE OF DEVELOPING INCREASED ALLERGY SYMPTOMS FROM EXPOSURE TO THIS PRODUCT.**

**Preventive Measures**

**PERSONAL PROTECTIVE EQUIPMENT....**

**EYES AND FACE: SAFETY GLASSES TO PROTECT EYES AND FACE.  
SKIN (HANDS, ARMS AND BODY): IMPERVIOUS GLOVES SHOULD BE WORN AT ALL TIMES WHEN HANDLING THIS PRODUCT. IMPERVIOUS CLOTHING SHOULD BE WORN WHERE RISK OF SKIN EXPOSURE IS MUCH HIGHER.**

**VENTILATION..... VENTILATION MUST BE SUFFICIENT TO CONTROL VAPOURS. LOCAL VENTILATION IS RECOMMENDED.**

**LEAK AND SPILL PROCEDURES..... ABSORB WITH SAND, SAWDUST.**

**WASTE DISPOSAL..... DISPOSE IN ACCORDANCE WITH MUNICIPAL, PROVINCIAL & FEDERAL REGULATIONS.**

**HANDLING PROCEDURES AND EQUIPMENT. AVOID SKIN CONTACT.**

**STORAGE REQUIREMENTS..... STORE AT ROOM TEMPERATURE**

**SPECIAL SHIPPING INFORMATION..... THIS PRODUCT IS NOT REGULATED UNDER TDG**

**First Aid Measures**

**SPECIFIC FIRST AID PROCEDURES.....**

**SKIN..... WASH WITH SOAP & WATER. REMOVE CONTAMINATED CLOTHING.  
EYES..... FLUSH EYES WITH PLENTY OF WATER. GET IMMEDIATE MEDICAL ATTENTION.  
INHALATION.... REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION AND SEEK MEDICAL ATTENTION.  
INGESTION..... DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION.**

**Preparation Date of Material Safety Data Sheet**

**PREPARED BY..... CHIEF CHEMIST  
PHONE NUMBER OF PREPARER..... 416-255-1111 FAX: 416-255-1729  
DATE PREPARED..... August 7, 2009**

**Flextile Ltd. assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, Flextile Ltd., assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in his use of the material.**

**...FLEXITILE LTD.**

**N/D = NOT DETERMINED**