

1600 RSG



PREMIUM RAPID-SET POLYMER-MODIFIED SANDED GROUT

DESCRIPTION

Flextile RSG Rapid-Set Polymer-Modified Sanded grout is a premium fast-setting, and colour-consistent grout.

Unique formulation ensures colour uniformity, and develops superior flexural and compressive strengths, exceeding ANSI A118.7 requirements.

Contains Flexfresh for mould and mildew resistance.

BASIC USES

- For grouting all types of ceramic tile, quarry tile, pavers, granite, slate, mosaics or brick where joints width is 1.5mm (1/16") to 2.5cm (1").
- For residential and commercial, floor and wall surfaces, interior and exterior, in dry or wet applications.
- For swimming pool, spas, water fountain applications, after fully cured.

FEATURES

- Fast setting, allows for foot traffic within 3 to 4 hours.
- Colour uniformity.
- Ultra strong.
- For interior or exterior use.
- Polymer additive provides colour richness and uniformity.
- Improved stain resistance.
- Smooth, tight surface for easier maintenance.
- With *Flexfresh™* technology. Revolutionary technology that helps to inhibit the growth of mildew, fungus and other bacteria causing odours and stains in construction materials.

LIMITATIONS

- Do not mix with latex grout additives, as this grout contains polymer additives.
- Use only on surfaces which are maintained at a temperature above 10°C (50°F) and below 35°C (95°F) during application and for at least 72 hours after application.
- Do not use when a highly chemical, impact and stain-resistant grout is required or in heavy industrial tile installations. Instead, use Flexepoxy 100, 100%-solids epoxy grout.
- Some types of glazed ceramic tiles, marble, granite and marble agglomerates can be permanently stained, scratched, dulled or damaged when grouted with pigmented grout or sanded grout formulas.
- Do a test patch prior to installation. Check with tile manufacturer to see if pre-sealing of tile is required. As various external factors beyond the control of Flextile Ltd. such as joint width variation, water quality and quantity in mixing and cleanup, temperature, humidity and cleaning procedures may affect the colour shading of the grout, consistent colour shade cannot be guaranteed.
- Refer to Flextile's Grouting Tips reference chart at www.flextile.net for further information on colour consistency.

LEED Points Contribution

MR Credit 5, Regional Materials*
IEQ Credit 4.1, Low-Emitting
Materials – Adhesives & Sealants
IEQ Credit 4.3, Low-Emitting
Materials – Flooring Systems
*May be eligible

LEED Points

Up to 2 points

1 point

1 point

TECHNICAL DATA at 23°C (73°F) and 50% humidity

Exceeds ANSI A118.6 & A118.7 requirements

Description	ANSI SPEC. MPa (psi)	TYPICAL RESULT MPa (psi)
Compressive Strength		
3 hrs		10.4 to 13.8 (1000 to 2,000)
24 hrs		13.8 to 20.7 (2000 to 3000)
7 days		27.6 to 31.0 (4000 to 4500)
28 days	> 20.7 (3000)	31.0 to 34.4 (4500 to 5000)
Shrinkage, 7 day	< 0.2 %	< 0.2 %
Water absorption 50% humidity to immersion	< 5.0 %	< 5.0 %
Water absorption immersion to dry	< 7.5 %	< 7.0 %

Typical Physical Properties

Description	
Pot Life	30 minutes to 1 hr
Initial Cure	2-3 hrs
Final Cure	28 days
Cleanability:	With water before material dries
VOCs	0 g/L
Shelf Life:	1 year from production date when stored in dry, heated conditions

Approximate Grout Coverage per 100ft² (9.3m²)

JOINT SIZE

Tile Dimensions	JOINT SIZE				
	1/16" (1.5 mm) Lbs (Kgs)	1/8" (3 mm) Lbs (Kgs)	1/4" (6 mm) Lbs (Kgs)	3/8" (10 mm) Lbs (Kgs)	1/2" (12 mm) Lbs (Kgs)
1" x 1" x 1/4" (25 x 25 x 6 mm)	23 (10.5)	46 (20.9)			
2" x 2" x 1/4" (50 x 50 x 6 mm)	12.5 (5.7)	25 (11.4)			
3" x 3" x 1/4" (75 x 75 x 6 mm)	8.5 (3.9)	17 (7.7)			
4-1/4" x 4-1/4" x 1/4" (108 x 108 x 6 mm)	6 (2.8)	12 (5.5)	24 (10.9)		
4" x 8" x 1/2" (100 x 200 x 12 mm)	10 (4.6)	20 (9.1)	38 (17.3)	56 (25.5)	72 (32.7)
6" x 6" x 1/4" (150 x 150 x 6 mm)	4.5 (2.1)	9 (4.1)	17 (7.7)	25 (11.4)	33 (15)
6" x 6" x 1/2" (150 x 150 x 12 mm)	9 (4.1)	18 (8.2)	34 (15.5)	50 (22.7)	66 (30)
8" x 8" x 3/8" (200 x 200 x 10 mm)	5 (2.3)	10 (4.5)	20 (9.1)	29 (13.2)	38 (17.3)
12" x 12" x 3/8" (300 x 300 x 10 mm)	3.5 (1.6)	7 (3.2)	13 (5.9)	20 (9.1)	26 (11.8)
13" x 13" x 3/8" (330 x 330 x 10 mm)	3 (1.4)	6 (2.7)	12 (5.5)	18 (8.2)	24 (10.9)
16" x 16" x 3/8" (406 x 406 x 10 mm)	2.5 (1.2)	5 (2.3)	10 (4.5)	15 (6.8)	20 (9.1)
18" x 18" x 3/8" (457 x 457 x 10 mm)	2.5 (1.2)	5 (2.3)	9 (4.1)	13 (5.9)	18 (8.2)
20" x 20" x 3/8" (508 x 508 x 10 mm)	2.9 (0.9)	4 (1.8)	8 (3.6)	12 (5.5)	16 (7.3)
24" x 24" x 3/8" (610 x 610 x 10 mm)	1.5 (0.7)	3 (1.4)	7 (3.2)	10 (4.5)	13 (5.9)

For job specific installation systems, recommendations, project warranty information, or for assistance with installation specifications, please contact Flextile's technical department.

Toronto, ON – Email: mzerey@flextile.net
Montreal, QC – Email: mzerey@flextile.net
Burnaby, BC – Email: mboldt@flextile.net

Toll Free 1-800-699-3623
Toll Free 1-800-699-3623
Toll Free 1-888-236-4486

Tel 1-416-255-1111
Tel 1-514-345-8666
Tel 1-604-420-4914

Fax 1-416-255-1729
Fax 1-514-345-8825
Fax 1-604-420-0936

INSTALLATION

PREPARATORY WORK

Ceramic tile surfaces must be clean and setting materials must be adequately cured prior to grouting. Remove spacers and rake out high ridges of setting material from tile joints prior to grouting to ensure uniform grout thickness. Tile joints must be clean and free of dirt, dust or other foreign matter prior to grouting. Do a test patch to see if pre-sealing of tile is required to avoid staining of the tile.

APPLICATION

Add Flextile RSG Premium Rapid-Set Polymer-Modified Sanded Grout to cool, clean water and mix by hand, or preferably with a slow speed mixer (maximum 150-RPM). Mix with the following proportions:

Water	Flextile RSG Premium Rapid-Set Polymer-Modified Sanded Grout
1.9 L (2 U.S. qts).	11.3 kg (25 lbs).

Do not use excess water for mixing, as this will negatively affect the final cure and appearance of the grout. Dampen surface of tile slightly with clean water before grouting to make spreading of grout easier. Spread grout with a hard rubber float, working diagonally to joints and using wrist action to fully pack the joints. Holding the float at 90° to the tile surface, use diagonal passes to remove excess grout from the surface. Finished grout joint should be flush with the edge of the square-edged tile, or tooled to the glazed edge of cushion-edged tile. Allow grout to sit until firm in the joints, approximately 20 to 30 minutes.

Use 2 buckets of clean water for cleaning, one for the initial cleaning, removing the excess grout, and the other for slight moistening of the grout sponge in final cleanup. Avoid leaving any excess water on the surface of grout joints during clean-up.

DO NOT use excess water for mixing or for cleanup as this can cause discoloration and soft/powdery joints. 1 to 2 hrs after application, buff the grouted surface with cheesecloth or a clean, dry cotton cloth when a haze is visible on the tile surface to remove any remaining surface water or grout residue.

CURING

Cure for a minimum of 3 hours prior to exposure to foot traffic, Protect from rain or water immersion until thoroughly dry. Sealing the grout is recommended but not mandatory. Follow the recommendations and instructions of the sealer manufacturer. To maintain a clean tile surface, use a neutral-pH cleaner for maintaining the floor, followed by a clean-water rinse. Do not use harsh chemicals to maintain the tile surface. Grout must be cured for at least 3 days prior to regular maintenance and cleaning.

CAUTION

Freshly mixed cement, mortar, concrete or grout may cause skin injury. Avoid extended contact with skin where possible and wash exposed skin areas promptly with water. If any cement or cement mixtures get into the eye, rinse immediately and repeatedly with water and get prompt medical attention. Keep out of reach of children.

SAFETY

Refer to Flextile Material Safety Data Sheet for detailed health and safety information.

AVAILABILITY AND COSTS

Flextile RSG Premium Polymer-Modified Sanded Grout is available from Flextile Ltd. and its distributors in 11.3 kg (25lb). Cost: Data supplied upon request.

WARRANTY

Flextile warrants that this product is of merchantable quality and is suitable for the purpose for which it is intended. Flextile's liability under this warranty shall be limited to replacement of its product found to be defective or, at its option, a refund of the purchase price.

MAINTENANCE

No maintenance is required except where damages result from unforeseen circumstances. Repair procedures shall be directed by Flextile or its distributors.

TECHNICAL SERVICES

Flextile maintains a well-equipped laboratory able to test its products in conjunction with the products with which they are used. Technical assistance for use of Flextile products is available upon request.

RELATED REFERENCES

Current editions of TTMAC 09 30 00 & TCNA Ceramic Tile Installation Manuals.

June 21, 2012

