

# TILE & GROUT CAULK

## DESCRIPTION & BASIC USES

Flexile Tile & Grout Caulk is a superior quality caulk specially designed to complement the Flexile Polymer-Modified Grout line. It is formulated with silicone for superior durability and adhesion.

## FEATURES

- Silicized Acrylic Formula.
- Moisture & Mildew Resistant.
- Excellent Durability.
- For Indoor or Outdoor Use.
- Available in Sanded and Non-Sanded Formulas.

## DIRECTIONS

1. Surfaces must be dry, clean and free of dust, dirt, mildew, oil and other foreign substances.
2. Cut spout to desired bead thickness.
3. Remove all old caulking before applying new caulk. Clean area with mild solution of bleach and water. Be sure area to be caulked is completely dry before applying caulk.
4. Apply caulk on surfaces which are maintained above 7°C (45°F), and below 49°C (120°F). Tool caulking within 10 minutes of application. Use wet finger or damp, smooth sponge.
5. Excess may be cleaned up with a damp cloth before caulk begins to skin over.
6. Caulk is fully cured in 3-5 days depending on temperature, humidity, and thickness of application. In humid or enclosed areas, i.e. enclosed shower, use a room fan to circulate air to assist in curing caulk.

## COVERAGE

Approximately 7.6M (25 ft) for 6mm (1/4").

## SAFETY

KEEP OUT OF REACH OF CHILDREN.

Refer to Flexile Material Safety Data Sheet for detailed health and safety information.

## AVAILABILITY AND COST

Flexile Tile & Grout Caulk is available from Flexile Ltd. and its distributors in cartridges of 310ml (10.3 fl. oz.).

Cost: Data supplied upon request.

## IMPORTANT

Mask or shield areas susceptible to staining. Test in a non-conspicuous area to see if staining will occur.

## MAINTENANCE

No maintenance is required except where damages result from unforeseen circumstances. Repair procedures shall be directed by Flexile or its distributors.

## TECHNICAL SERVICES

Flexile maintains a well-equipped laboratory able to test its products in conjunction with the products with which they are used. Technical assistance for use of Flexile products is available upon request.

## RELATED REFERENCES

Current editions of: Ceramic Tile Installation Manual (09300) from the TTMAC & TCA Ceramic Tile Installation Handbook.