

**FLEXTILE GROUTS**  
**REFERENCE CHART**

	<b>500 UNSANDED GROUTS</b>	<b>600 SANDED GROUTS</b>	<b>FLEXEPOXY 100 100% EPOXY</b>	<b>COLOURMAX POLYURETHANE GROUT TECHNOLOGY</b>
COLOURS	36	36	13	17
GROUT JOINT WIDTHS	1.5-3mm 1/16"-1/8"	3-12mm 1/8"-1/2"	1.5-12mm 1/16"-1/2"	1.5-12mm 1/16"-1/2"
ONE-COMPONENT / READY TO USE				√
INDUSTRIAL APPLICATIONS			√	√
COMMERCIAL APPLICATIONS	√	√	√	√
RESIDENTIAL APPLICATIONS	√	√	√	√
INTERIOR	√	√	√	√
EXTERIOR		√		√
CHEMICAL RESISTANT			√	√
STAIN RESISTANT			√	√
NONSAGGING	√	√	√	√
NONSHRINKING	√	√	√	√
LEED COMPLIANT	√	√	√	√
LIGHT FOOT TRAFFIC	24hrs.	24hrs.	24hrs.	24hrs.
HEAVY FOOT TRAFFIC	48hrs.	48hrs.	24hrs	48hrs.
INITIAL SET at 21°C (70°F)	30min	30min	2hrs	2hrs.
FULL CURE	28days	28days	14days	14days