

FLEXTILE LTD
Material Safety Data Sheet
41 MORTAR ADDITIVE

Material Identification and Use

MANUFACTURER/SUPPLIER'S NAME..... FLEXTILE LTD.
MANUFACTURER'S ADDRESS..... 121-30TH STREET, ETOBICOKE, ONT. M8W 3C1
MANUFACTURER'S PHONE NUMBER..... (416)255-1111 TollFree 1-800-699-3623 FAX: (416)255-1729
IN CASE OF CHEMICAL EMERGENCY..... CALL CANUTEC (613) 996-6666
PRODUCT IDENTIFIER..... 41 MORTAR ADDITIVE.
PRODUCT USE..... USE AS AN ADDITIVE TO BE MIXED WITH CEMENT AND SAND AND
USE AS A SETTING BED.
WHMIS CLASSIFICATION..... NOT REGULATED UNDER WHMIS

Hazardous Ingredients of Materials

CHEMICAL IDENTITY	CONCENTRATION	CAS#/NA#/UN#	LD(50)	LC(50)
THIS PRODUCT CONTAINS NO HAZARD INGREDIENTS AS DEFINED BY THE OSHA HAZARD COMMUNICATION STANDARD 29 CFR 1910.1200 OR SECTION 13 OF THE CANADIAN HAZARDOUS PRODUCT ACT.				
ALL INGREDIENTS ARE LISTED WITHIN OR EXEMPTED FROM US TSCA AND CANADIAN DSL.				

Physical Data For Product

PHYSICAL STATE.....	LIQUID			
ODOUR & APPEARANCE.....	MILKY WHITE LIQUID - SLIGHT ODOUR OF LATEX.			
ODOUR THRESHOLD.....	NOT AVAILABLE			
SPECIFIC GRAVITY.....	1.03	VAPOUR PRESSURE.....	N/D	
VAPOUR DENSITY (air=1).....	N/D	EVAPORATION RATE.....	N/D	
BOILING POINT.....	100C	FREEZING POINT.....	N/D	
pH.....	9-10	DENSITY (g/ml).....	N/D	
CALCULATED VOC	0 gm/litre			

Fire and Explosion Hazard of Product

CONDITIONS OF FLAMMABILITY.....	STABLE
MEANS OF EXTINCTION.....	WATER, FOG & DRIED POLYMER
FLASHPOINT AND METHOD OF DETERMINATION.....	NONE
UPPER EXPLOSION LIMIT (% BY VOL)..	N/D
LOWER EXPLOSION LIMIT (% BY VOL)..	N/D
AUTO-IGNITION TEMPERATURE.....	N/D
FLAMMABILITY CLASSIFICATION.....	NON FLAMMABLE
HAZARDOUS COMBUSTION PRODUCTS.....	N/D
EXPLOSION DATA.....	MATERIAL CAN SPLATTER ABOVE 100C. DRIED POLYMER IS COMBUSTIBLE.
SENSITIVITY TO STATIC DISCHARGE...	N/D

Reactivity Data

CHEMICAL STABILITY.....	STABLE
INCOMPATIBLE MATERIALS.....	STRONG OXIDISING AGENTS, STRONG ACIDS AND STRONG BASES.
CONDITIONS TO AVOID.....	NONE KNOWN
HAZARDOUS DECOMPOSITION PRODUCTS..	C0, C02, OXIDES OF NITROGEN AND OTHER UNIDENTIFIED ORGANIC COMPOUNDS.
POLYMERIZATION:	WILL NOT OCCUR

41 MORTAR ADDITIVE

Toxicological Properties of Product

ROUTES OF ENTRY

SKIN CONTACT.....	MODERATELY IRRITATING TO THE SKIN.
SKIN ABSORPTION.....	NO DATA
EYE.....	IRRITATING TO EYES.
INHALATION.....	VAPOUR OR MIST CAN CAUSE HEADACHE, NAUSEA AND IRRITATION OF THE NOSE, THROAT AND LUNGS.
INGESTION.....	LOW SINGLE DOSE TOXICITY.
ACUTE OVER EXPOSURE EFFECTS.....	AS ABOVE.
CHRONIC OVER EXPOSURE EFFECTS...	N/D
EXPOSURE LIMITS.....	N/D
IRRITANCY OF PRODUCT.....	N/D
SENSITIZATION TO MATERIAL.....	N/D
CARCINOGENICITY, REPRODUCTIVE EFFECTS.....	N/D
TERATOGENICITY, MUTAGENICITY...	N/D
TOXICOLOGICALLY SYNERGISTIC PRODUCTS.....	N/D

Preventive Measures

PERSONAL PROTECTIVE EQUIPMENT.....	VENTILATE ADEQUATELY, OTHERWISE WEAR AN APPROPRIATE BREATHING APPARATUS. OSHA/NIOSH APPROVED RESPIRATOR. AVOID SPLASHES. WEAR A FACE SHIELD OR SAFETY GLASSES WITH SIDE SHIELDS. WEAR IMPERVIOUS RUBBER GLOVES. WEAR WORK CLOTHING COVERING ARMS AND LEGS.
VENTILATION.....	LOCAL (EXHAUST) VENTILATION.
LEAK AND SPILL PROCEDURES.....	ABSORB WITH PAPER, SAND OR SAWDUST. DISPOSE INTO A DISPOSAL CONTAINER.
WASTE DISPOSAL.....	DISPOSE OF WASTE ACCORDING TO MUNICIPAL, PROVINCIAL AND FEDERAL REGULATIONS
HANDLING PROCEDURES AND EQUIPMENT.	WEAR AN EYE PROTECTION APPARATUS. AVOID PROLONGED OR REPEATED SKIN CONTACT. AVOID BREATHING VAPOURS.
STORAGE REQUIREMENTS.....	STORE IN A TIGHTLY SEALED CONTAINER AND KEEP STORAGE TEMPERATURE AT 16-35C.
SPECIAL SHIPPING INFORMATION.....	NOT REGULATED

First Aid Measures

SPECIFIC FIRST AID PROCEDURES.....	FLUSH EYES AND CONTAMINATED SKIN WITH PLENTY OF WATER. IN CASE OF DISCOMFORT BY VAPOURS OR DUST, MOVE TO A VENTILATED AREA. IN CASE OF INGESTION, INDUCE VOMITING. SEEK MEDICAL ATTENTION.
------------------------------------	--

Preparation Date of Material Safety Data Sheet

PREPARED BY.....	CHIEF CHEMIST
PHONE NUMBER OF PREPARER.....	(416) 255-1111 FAX: (416) 255-1729
DATE PREPARED.....	04 August 2009

Flextile Ltd. assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, Flextile Ltd., assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in his use of the material.

...FLEXITILE LTD.

N/D = NOT DETERMINED