

FLEXITILE LTD
Material Safety Data Sheet

770 ULTRA-QUICK MULTI-PURPOSE FLOORING ADHESIVE

Material Identification and Use

MANUFACTURER/SUPPLIER'S NAME.....	FLEXITILE LTD.
MANUFACTURER'S ADDRESS.....	121-30TH STREET, ETOBICOKE, ONT. M8W 3C1
MANUFACTURER'S PHONE NUMBER.....	(416)255-1111 Toll-Free 1-800-699-3623 FAX: (416)255-1729
IN CASE OF CHEMICAL EMERGENCY.....	CALL CANUTEC (613) 996-6666
PRODUCT IDENTIFIER.....	770 ULTRA_QUICK MULTI-PURPOSE FLOORING ADHESIVE.
PRODUCT USE.....	A QUALITY, LATEX/RESIN, MULTI-PURPOSE FLOORING ADHESIVE.
WHMIS CLASSIFICATION.....	NOT REGULATED UNDER WHMIS

Hazardous Ingredients of Materials

CHEMICAL IDENTITY	CONCENTRATION	CAS#/NA#/UN#	OSHA (PEL)	ACGIH (TLV-TWA)
THIS PRODUCT CONTAINS NO HAZARDOUS INGREDIENT AS DEFINED BY US OSHA HAZARD COMMUNICATION STANDARD - 29 CFR 1910.1200 OR SECTION 13 OF THE CANADIAN HAZARDOUS PRODUCT ACT.				
All ingredients are listed within or exempted from US TSCA (TOXIC SUBSTANCE CONTROL ACT)and Canadian DSL.				

Physical Data For Product

PHYSICAL STATE.....	VISCOUS LIQUID		
ODOUR AND APPEARANCE.....	MILD ODOUR, CREAM COLOURED VISCOUS LIQUID		
ODOUR THRESHOLD.....	NOT DETERMINED		
SPECIFIC GRAVITY.....	1.1		
VAPOUR PRESSURE.....	N/D	VAPOUR DENSITY (air=1).....	N/D
EVAPORATION RATE(Butyl Acetate=1)...	Same as water	BOILING POINT.....	100°C (212°F)
FREEZING POINT.....	N/D	pH.....	9-10
VOC CONTENT	0 gm/L		

Fire and Explosion Hazard of Product

CONDITIONS OF FLAMMABILITY.....	NON-COMBUSTIBLE
MEANS OF EXTINCTION.....	Will not burn except under extreme temperature. Water spray, CO₂, dry chemical or foam
FLASHPOINT.....	>100°C (212°F)
UPPER EXPLOSION LIMIT (% BY VOL)..	N/D
LOWER EXPLOSION LIMIT (% BY VOL)..	N/D
AUTO-IGNITION TEMPERATURE.....	N/D
HAZARDOUS COMBUSTION PRODUCTS.....	CO₂, CO, FUMES
EXPLOSION DATA.....	N/D
SENSITIVITY TO STATIC DISCHARGE...	N/D
SPECIAL FIRE FIGHTING PROCEDURES....	Wear standard fire fighting gear with self-contained breathing apparatus.

Reactivity Data

CHEMICAL STABILITY.....	STABLE
INCOMPATIBLE MATERIALS.....	STRONG ACIDS, STRONG BASES & STRONG OXIDISING AGENTS.
CONDITIONS TO AVOID.....	NONE KNOWN.
HAZARDOUS DECOMPOSITION PRODUCTS..	BURNING MAY PRODUCE CO AND/OR CO₂.
HAZARDOUS POLYMERIZATION.....	WILL NOT OCCUR.

770 ULTRA-QUICK MULTI-PURPOSE FLOORING ADHESIVE

Toxicological Properties of Product

ROUTES OF ENTRY

SKIN CONTACT.....	MAY CAUSE IRRITATION ON PROLONGED CONTACT.
SKIN ABSORPTION.....	N/D
EYE.....	IRRITATING TO EYES.
INHALATION.....	MAY CAUSE DISCOMFORT.
INGESTION.....	MAY BE TOXIC IS SWALLOWED.
ACUTE OVER EXPOSURE EFFECTS.....	... AS ABOVE.
CHRONIC OVER EXPOSURE EFFECTS.....	N/D
EXPOSURE LIMITS.....	N/D
IRRITANCY OF PRODUCT.....	N/D
SENSITIZATION TO MATERIAL.....	N/D
CARCINOGENICITY, REPRODUCTIVE EFFECTS.....	N/D
TERATOGENICITY, MUTAGENICITY.....	N/D
TOXICOLOGICALLY SYNERGISTIC PRODUCTS.....	N/D

Preventive Measures

PERSONAL PROTECTIVE EQUIPMENT.....	WEAR IMPERVIOUS RUBBER GLOVES.
VENTILATION.....	USE A LOCAL (EXHAUST) VENTILATION.
LEAK AND SPILL PROCEDURES.....	ABSORB WITH AN INERT MATERIAL; SAND OR SAWDUST. SCRAPE UP AND DISPOSE INTO A DISPOSAL CONTAINER. WET MATERIAL IS DISPERSIBLE IN SOAPY WATER. PREVENT WASHING WATER FROM ENTERING WATERWAYS.
WASTE DISPOSAL.....	DISPOSE IN ACCORDANCE WITH MUNICIPAL, PROVINCIAL AND FEDERAL REGULATIONS.
HANDLING PROCEDURES AND EQUIPMENT.....	AVOID EYE CONTACT.
STORAGE REQUIREMENTS.....	STORE AT 60-95°F (15-35°C) AND OUT OF THE SUN. USE ADEQUATE VENTILATION TO AVOID BREATHING VAPOURS WHEN COVER IS REMOVED. PROTECT FROM FREEZING.
SPECIAL SHIPPING INFORMATION.....	NOT REGULATED

First Aid Measures

FIRST AID PROCEDURES...
IMMEDIATELY FLUSH EYES WITH ABUNDANT WATER FOR AT LEAST 15 MINUTES, FORCIBLY HOLDING EYELIDS APART. SEEK MEDICAL ATTENTION. IN CASE OF INHALATION, REMOVE TO FRESH AIR. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION. IN CASE OF SKIN CONTACT, REMOVE ANY CONTAMINATED CLOTHING AND WASH AFFECTED AREA WITH SOAP & WATER. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION. IN CASE OF INGESTION, DO NOT INDUCE VOMITING. SEEK MEDICAL ATTENTION.

Preparation Date of Material Safety Data Sheet

PREPARED BY.....	ADHESIVE CHEMIST
PHONE NUMBER OF PREPARER.....	416-255-1111 FAX: 416-255-1729
DATE PREPARED.....	4 August 2009

Flextile Ltd. assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, Flextile Ltd., assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in his use of the material.

...FLEXITILE LTD.

N/D = NOT DETERMINED