

FLEXTILE LTD
Material Safety Data Sheet

FLEXTECH 700 SUPERIOR QUALITY MULTI-PURPOSE FLOORING ADHESIVE

Material Identification and Use

MANUFACTURER/SUPPLIER'S NAME.....	FLEXTILE LTD.
MANUFACTURER'S ADDRESS.....	121-30TH STREET, ETOBICOKE, ONT. M8W 3C1
MANUFACTURER'S PHONE NUMBER.....	416-255-1111 Toll-Free 1-800-699-3623 FAX: 416-255-1729
IN CASE OF CHEMICAL EMERGENCY.....	CALL CANUTEC (613) 996-666
PRODUCT IDENTIFIER.....	FLEXTECH 700 SUPERIOR QUALITY MULTI-PURPOSE FLOORING ADHESIVE
PRODUCT USE.....	FOR INSTALLATION OF VINYL COMPOSITION TILE, SHEET VINYL & CARPET.
WHMIS CLASSIFICATION.....	NOT REGULATED UNDER WHMIS

Hazardous Ingredients of Materials

CHEMICAL IDENTITY	CONCENTRATION	CAS#/NA#/UN#	OSHA (PEL)	ACGIH (TLV-TWA)
THIS PRODUCT CONTAINS NO HAZARDOUS INGREDIENT AS DEFINED BY US OSHA HAZARD COMMUNICATION STANDARD - 29 CFR 1910.1200 OR SECTION 13 OF THE CANADIAN HAZARDOUS PRODUCT ACT.				
All ingredients are listed within or exempted from US TSCA and Canadian DSL.				

Physical Data For Product

PHYSICAL STATE.....	VISCOUS LIQUID		
ODOUR AND APPEARANCE.....	MILD ODOUR, CREAM COLOURED VISCOUS LIQUID		
ODOUR THRESHOLD.....	NOT DETERMINED		
SPECIFIC GRAVITY.....	1.1		
VAPOUR PRESSURE.....	N/D	VAPOUR DENSITY (air=1).....	N/D
EVAPORATION RATE(Butyl Acetate=1)...	Same as water	BOILING POINT.....	212°F (100°C)
FREEZING POINT.....	N/D	pH.....	9-10
CALCULATED VOC.....	0 gm/litre		

Fire and Explosion Hazard of Product

CONDITIONS OF FLAMMABILITY.....	NON-COMBUSTIBLE
MEANS OF EXTINCTION.....	Will not burn except under extreme temperature. Water spray, CO₂, dry chemical or foam
FLASHPOINT.....	>212°F (100°C)
UPPER EXPLOSION LIMIT (% BY VOL)..	N/D
LOWER EXPLOSION LIMIT (% BY VOL)..	N/D
AUTO-IGNITION TEMPERATURE.....	N/D
HAZARDOUS COMBUSTION PRODUCTS.....	CO₂, CO, FUMES
EXPLOSION DATA.....	N/D
SENSITIVITY TO STATIC DISCHARGE...	N/D
SPECIAL FIRE FIGHTING PROCEDURES....	Wear standard fire fighting gear with self-contained breathing apparatus.

Reactivity Data

CHEMICAL STABILITY.....	STABLE
INCOMPATIBLE MATERIALS.....	STRONG ACIDS, STRONG BASES & STRONG OXIDISING AGENTS.
CONDITIONS TO AVOID.....	NONE KNOWN.
HAZARDOUS DECOMPOSITION PRODUCTS..	BURNING MAY PRODUCE CO AND/OR CO₂.
HAZARDOUS POLYMERIZATION.....	WILL NOT OCCUR.

FLEXTECH 700 SUPERIOR QUALITY MULTI-PURPOSE FLOORING ADHESIVE

Toxicological Properties of Product

ROUTES OF ENTRY

SKIN CONTACT.....	MAY CAUSE IRRITATION ON PROLONGED CONTACT
SKIN ABSORPTION.....	NO EVIDENCE OF ADVERSE EFFECTS FROM AVAILABLE INFORMATION.
EYE.....	MAY CAUSE IRRITATION
INHALATION.....	MAY CAUSE HEADACHE, NAUSEA, VOMITING AND IRRITATION OF THE RESPIRATORY TRACT.
INGESTION.....	MAY CAUSE ABDOMINAL DISCOMFORT OR PAIN, NAUSEA AND VOMITING. MAY BE FATAL IF LARGE VOLUMES ARE SWALLOWED.

EFFECTS OF ACUTE EXPOSURE ... REFER TO ROUTE OF ENTRY.
EFFECTS OF CHRONIC EXPOSURE.. REPEATED CONTACT WITH SKIN MAY CAUSE DERMATITIS IN SENSITIVE INDIVIDUALS. PROLONGED INHALATION MAY PRODUCE SIGN OF CENTRAL NERVOUS SYSTEM INVOLVEMENT, PARTICULARLY DIZZINESS AND NYSTAGMUS.

IRRITANCY OF PRODUCT..... N/D SENSITIZATION TO MATERIAL..... N/D

CARCINOGENICITY, REPRODUCTIVE EFFECTS: NO EVIDENCE THAT IT HAS CAUSED BIRTH DEFECTS IN HUMANS.

TERATOGENICITY, MUTAGENICITY.... MINIMAL EVIDENCE OF TERATOGENICITY.

TOXICOLOGICALLY SYNERGISTIC RODUCTS..... N/D

Preventive Measures

PERSONAL PROTECTIVE EQUIPMENT....	RUBBER GLOVES, RESPIRATOR IN ENCLOSE AREAS.
VENTILATION.....	ADEQUATE VENTILATION
LEAK AND SPILL PROCEDURES.....	SOAK UP WITH AN ABSORBENT MATERIAL. CLEAN WITH WATER. LET DRY. MAY CLOG SEWERS.
WASTE DISPOSAL.....	DISPOSE IN ACCORDANCE WITH MUNICIPAL, PROVINCIAL AND FEDERAL REGULATIONS.
HANDLING PROCEDURES AND EQUIPMENT.	AVOID EYE CONTACT, REPEATED OR PROLONGED SKIN CONTACT AND INHALING VAPOURS.
STORAGE REQUIREMENTS.....	STORE AT 60-95°F (15-35°C) AND OUT OF THE SUN. USE ADEQUATE VENTILATION TO AVOID BREATHING VAPOURS WHEN COVER IS REMOVED. PROTECT FROM FREEZING.
SPECIAL SHIPPING INFORMATION.....	NOT REGULATED

FIRST AID MEASURES

FIRST AID PROCEDURES..

IMMEDIATELY FLUSH EYES WITH ABUNDANT WATER FOR AT LEAST 15 MINUTES, FORCIBLY HOLDING EYELIDS APART. SEEK MEDICAL ATTENTION. IN CASE OF INHALATION, REMOVE TO FRESH AIR. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION. IN CASE OF SKIN CONTACT, REMOVE ANY CONTAMINATED CLOTHING AND WASH AFFECTED AREA WITH SOAP & WATER. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION. IN CASE OF INGESTION, DO NOT INDUCE VOMITING. SEEK MEDICAL ATTENTION.

PREPARATION DATE OF MATERIAL SAFETY DATA SHEET

PREPARED BY.....	CHIEF CHEMIST
PHONE NUMBER OF PREPARER.....	416 - 255-1111 EXT 235 FAX: 416 - 255-1729
DATE PREPARED.....	4 August 2009

Flextile Ltd. assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, Flextile ltd., assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in his use of the material.

...FLEXITILE LTD.

N/D = NOT DETERMINED